

Specification

Model No.	LCHC05W	
System	Main Processor	High Performance Embedded Microprocessor Hi3507
	Operating system	Embedded Linux OS
Image Sensor	Image Sensor	CMOS Sensor, 0.3 Megapixel.
	Lens	3.6mm (IR lens)
	Lens Vieing Angle	90°
	Min. Illumination	0LUX/F1.2(when IR on)
	Night vision	12pcs IR LEDs, Night visibility up to 10meters
IR-Cut	Built-in IR Cut,With self-check function,Double optical fliter automatic switch, no color deviation indoor or outdoor.	
Video	Video Compression	H.264
	Signal System	PAL/NTSC
	Frame Rate	PAL: 25 fps, NTSC: 30 fps
	Video Resolution	VGA(640*480)
	Video output	BT656/3.5 inch high definition display
	Video Call	Realize the video call between two cameras or among Android, iOS Mobile Terminal Device and camera.
	Scree shoots	YES
Audio	Compression	AMR
	Audio Input	Built-in microphone or an external headset
	Audio Output	Built-in speakers or an external headset
Recording Manager	Recording Mode	Manual/Timer/Motion/Schedule
	Local Storage	Support USB Disk, Micro SD card.
Pan/Tilt	Rotation Angle	Pan:355°, Tilt: 60°
Alarm	Alarm Input	Learning wireless sensor alarm input
	Alarm Triggered	Speakers alarm,Alarm recording,Capture,Email,Phone push alarm
Interface	Ethernet Interface	RJ-45 interface ,10/100M self-adaption
	USB	1* USB 2.0
	TF	1*TF
	Wifi	802.11 b/g/n, Support WEP,WPA,WPA2 Encryption
	Power	DC5V/2A

	PTZ control	Built-in horizontal and vertical control motor	
Others	Product Type	Plastic shell, Cartoon Robot/ Indoor use	
	Working Temperature	0~55°C	
	Working Humidity	10%-90% RH	
	Power Consumption	2W	
	Size	Item Size:	
		Package size:	150mm*95mm*160mm (L*W*H)
	Weight	Net weight: 500 g, gross weight: 800 g(Note:Actual Weight Final)	
	Accessories	1*Adaptor, 1*3C card, 1*Antenna, 1* User Manual	
Certification	Certification	CE, FCC, RoHS	